

## Countersunk Head Articulated Bolt For Insulated Glass Units ( Model: KSP.R1001A-V-1465 )




**Attributes:**

**Product Code:** KSP.R1001A-V-1465

**Unit Of Sale:** Each

**Dimensions**




**Components**




MARK.	QUANTITY	DESCRIPTION	REFERENCE
1	1	Sessel body	32 Cr Ni Mo 17-12,2 as per EN 10088-5
2	1	Threaded Axis	32 Cr Ni Mo 19,5 1 as per EN 10088-5
3	1	Steel ring grommet	AW 3000 as per EN 17533-3:2015
4	1	Contact washer	White polypropylene/polypropylene
5	1	Contact ring	32 Cr Ni Mo 17-12,2 as per EN 10088-5
6	1	Nut DIN 934	A4
7	2	Washer	A4
8	1	Lock washer DIN 127	A4
9	1	Nut DIN 934	A4
10	1	3025 Cap-nut - Option	32 Cr Ni Mo 17-12,2 as per EN 10088-5
11	1	Mordil cap-nut - Option	32 Cr Ni Mo 17-12,2 as per EN 10088-5
12	1	Spoking ring	ACU44465/2017A (ALU63) as per EN-573-3

**How to Use**



It is required to provide the following information with each request for price quotation: 1. 15mm minimum, 5.8 & maximum, 13.5-15.5 (14) thickness for single and double if the thickness is 16 or greater dimension (DIN 18 253) (the thickness of the glass) 2. To avoid to request, the thickness of the existing support on the edge of the glass.

**Method of Performance**



Displacement	Full Load
0mm	0N
100mm	1000N
200mm	2000N
300mm	3000N
400mm	4000N
500mm	5000N
600mm	6000N
700mm	7000N
800mm	8000N
900mm	9000N
1000mm	10000N

1. 15mm minimum, 5.8 & maximum, 13.5-15.5 (14) thickness for single and double if the thickness is 16 or greater dimension (DIN 18 253) (the thickness of the glass) 2. To avoid to request, the thickness of the existing support on the edge of the glass.