

Countersunk Fixed Bolt For 15 - 22mm Thick Glass (Model: KSP.V2001-1522-1465)



- Fixed bolt with a countersunk head for use in spider glazing systems.
- Manufactured using 316 grade stainless steel.
- Standard 65mm long axis and suitable for 15 - 22mm thick glass.
- Please see the other bolts in the range for additional glass thicknesses.
- Special dimension glass bolts available on request.
- Glassparts recommend using thread locking compound whenever possible.

Attributes:

Product Code: KSP.V2001-1522-1465

Unit Of Sale: Each

Components

MARK	QUANTITY	DESCRIPTION	MATERIAL
1	1	Body	X2 Cr Ni Mo 17-12,2 as per EN 10088-3
2	1	Threaded plate	Alu
3	1	Glass hole general	AW 1000A as per EN 573-3 / AS 3558
4	1	Conical spacer	Alu (optional) or Alu (optional)
5	1	Glass cut Ø 60	X2 Cr Ni Mo 17-12,2 as per EN 10088-3
6	1	Nut EN 204	Alu
7	2	Washer	Alu
8	1	Lock washer 12°	Alu
9	1	Nut EN 204	Alu
10	1	3025 Cap Nut - Option	X2 Cr Ni Mo 17-12,2 as per EN 10088-3
11	1	3025 Cap Nut - Option	X2 Cr Ni Mo 17-12,2 as per EN 10088-3

Glass Drilling

Monolithic glass

Laminated glass

V = 1st glass + intercalated film + 2nd glass

Available for glass thicknesses from 8 to 31.52mm, for other thicknesses please consult us.
It is important to provide the following information with each request: the glass composition (ex: 10mm monolithic, 6.8+2-12-12 laminating), the length and diameter of the threaded axis (if not standard dimensions (M1.6, G1mm)), the reference of the spider to be used as support, or the thickness of an existing support for the delivery of the spacer.

Technical Parameters

Identifying capacity	Not out
Ø 10	Ø 10
Ø 12	Ø 12
Ø 14	Ø 14
Ø 16	Ø 16
Ø 18	Ø 18
Ø 20	Ø 20
Ø 22	Ø 22
Ø 24	Ø 24
Ø 26	Ø 26
Ø 28	Ø 28
Ø 30	Ø 30
Ø 32	Ø 32
Ø 34	Ø 34
Ø 36	Ø 36
Ø 38	Ø 38
Ø 40	Ø 40
Ø 42	Ø 42
Ø 44	Ø 44
Ø 46	Ø 46
Ø 48	Ø 48
Ø 50	Ø 50
Ø 52	Ø 52
Ø 54	Ø 54
Ø 56	Ø 56
Ø 58	Ø 58
Ø 60	Ø 60
Ø 62	Ø 62
Ø 64	Ø 64
Ø 66	Ø 66
Ø 68	Ø 68
Ø 70	Ø 70
Ø 72	Ø 72
Ø 74	Ø 74
Ø 76	Ø 76
Ø 78	Ø 78
Ø 80	Ø 80
Ø 82	Ø 82
Ø 84	Ø 84
Ø 86	Ø 86
Ø 88	Ø 88
Ø 90	Ø 90
Ø 92	Ø 92
Ø 94	Ø 94
Ø 96	Ø 96
Ø 98	Ø 98
Ø 100	Ø 100

100% Traceability (Lot/Date) - Used at 100% determination
100% Ultrasonic test (done - used at 100% determination)
Values are given without factor of safety