

**60mm Dia. Flat Head Fixed Bolt For 8 - 15mm Thick Glass ( Model: KSP.V2005-0815-1266 )**




- Fixed bolt with a 60mm diameter flat head for use in spider glazing systems.
- Manufactured using 316 grade stainless steel.
- Standard 65mm long axis and suitable for 8 - 15mm thick glass.
- Please see the other bolts in the range for additional glass thicknesses.
- Special dimension glass bolts available on request.
- Glassparts recommend using thread locking compound whenever possible.

**Attributes:**


**Product Code:** KSP.V2005-0815-1266

**Unit Of Sale:** Each

**Dimensions**




**Components**




MARK	QUANTITY	DESIGNATION	MATERIAL
1	1	Body	316 Cr Ni Mo 17.12.22 sp per EN 10088-3
2	1	Threaded sleeve	Alu
3	1	Glass hole grommet	AW 10554 sp per EN 1733-3 / AW 105 516
4	2	Contact washer	W40 copper/Al or Cu/Al or Cu/Al
5	1	Glass hole O-ring	316 Cr Ni Mo 17.12.22 sp per EN 10088-3
6	1	Nut EN 1024	Alu
7	2	Washer	Alu
8	1	Lock washer 127	Alu
9	1	Nut EN 1024	316 Cr Ni Mo 17.12.22 sp per EN 10088-3
10	1	3025 Cap Nut - Option	316 Cr Ni Mo 17.12.22 sp per EN 10088-3
11	1	M14 Cap Nut - Option	316 Cr Ni Mo 17.12.22 sp per EN 10088-3

**How to Use**



**Technical Information**



Available for glass thickness from 8 to 17.00mm, for other thicknesses please contact us.  
 It is important to provide the following information when you request: the glass composition (tempered, laminated, heat-treated, etc.), the glass thickness, the glass type (float, etc.), the intended use of the bolt (to be used as support, or for the fixation of an existing support for the stability of the glass).  
 \*The glass hole diameter of the threaded part for standard dimensions (M14 - M16) is the reference of the spider to be used as support. The glass hole diameter of the threaded part for standard dimensions (M14 - M16) is the reference of the spider to be used as support. The glass hole diameter of the threaded part for standard dimensions (M14 - M16) is the reference of the spider to be used as support. The glass hole diameter of the threaded part for standard dimensions (M14 - M16) is the reference of the spider to be used as support.