

**GRABO Replacement Slender Seal ( Model: B0007.SLENDERSEAL )**


- The Grabo Sender Seal allows you to lift thinner and longer materials with ease and comfort.
- The unique design of the GRABO Slender Seal means it's even easier to grab surfaces with extended, narrow surface areas, such as pavers, long tiles, pipes, cut-to-size bench tops, curb stones, and more.



**Attributes:**

**Product Code:** B0007.SLENDERSEAL

**Unit Of Sale:** Each



**Lifting Capacity:**

Material	Perpendicular Hold Z		Parallel Hold X		Parallel Hold Y	
	Maximum Load	Safe Load	Maximum Load	Safe Load	Maximum Load	Safe Load
Glass	225 lbs (100 kg)	110 lbs (50 kg)	110 lbs (50 kg)	55 lbs (25 kg)	200 lbs (90 kg)	100 lbs (45 kg)
Metal	240 lbs (108 kg)	120 lbs (54 kg)	120 lbs (54 kg)	60 lbs (27 kg)	210 lbs (95 kg)	105 lbs (47 kg)
Wood	132 lbs (60 kg)	66 lbs (30 kg)	66 lbs (30 kg)	33 lbs (15 kg)	176 lbs (80 kg)	88 lbs (40 kg)
Rough Concrete	105 lbs (48 kg)	52.5 lbs (24 kg)	110 lbs (50 kg)	55 lbs (25 kg)	200 lbs (90 kg)	100 lbs (45 kg)

**Specifications:**

Black foam seal	
Material	SBR rubber foam sponge
Color	Black
L x W x H	16.2 x 4.5 x 1.24" (411 x 115 x 31.5 mm)
Dimensions of seal	371 x 65 mm
Density	10.6 lbs/cu ft (270 kg/m <sup>3</sup> )
Hardness, Shore C	~30 x ±2
Tearing Pressure	1800 Psi (128 kg/cm <sup>2</sup> )
Compression to 25% size at 100% (Compressive 48% performance reduction)	8.5 Psi (6000 kg/m <sup>2</sup> )
Water Absorption, %	<±5
Shrinkage at 160F (70C) for 24 hrs, %	<±20
Recommended Storage Temperature	Room temperature
Red seal	
Material	Silicon Foam
Color	Red
Density	43.1 lbs/cu ft (1050 kg/m <sup>3</sup> )
Hardness, Shore C	50-41-5
Water Absorption, %	<±4
Recommended Storage Temperature	Room temperature
Full seal	
Features	Composed seal on plastic frame Slender profile