

**GRABO Replacement Slender Seal ( Model: B0007.SLENDERSEAL )**


- The Grabo Sender Seal allows you to lift thinner and longer materials with ease and comfort.
- The unique design of the GRABO Slender Seal means it's even easier to grab surfaces with extended, narrow surface areas, such as pavers, long tiles, pipes, cut-to-size bench tops, curb stones, and more.



**Attributes:**

**Product Code:** B0007.SLENDERSEAL

**Unit Of Sale:** Each



**Lifting Capacity:**

| Material       | Perpendicular Hold Z |                     | Parallel Hold X    |                   | Parallel Hold Y    |                    |
|----------------|----------------------|---------------------|--------------------|-------------------|--------------------|--------------------|
|                | Maximum Load         | Safe Load           | Maximum Load       | Safe Load         | Maximum Load       | Safe Load          |
| Glass          | 225 lbs<br>(100 kg)  | 110 lbs<br>(50 kg)  | 110 lbs<br>(50 kg) | 55 lbs<br>(25 kg) | 200 lbs<br>(90 kg) | 100 lbs<br>(45 kg) |
| Metal          | 240 lbs<br>(108 kg)  | 120 lbs<br>(54 kg)  | 120 lbs<br>(54 kg) | 60 lbs<br>(27 kg) | 210 lbs<br>(95 kg) | 105 lbs<br>(47 kg) |
| Wood           | 132 lbs<br>(60 kg)   | 66 lbs<br>(30 kg)   | 66 lbs<br>(30 kg)  | 33 lbs<br>(15 kg) | 176 lbs<br>(80 kg) | 88 lbs<br>(40 kg)  |
| Rough Concrete | 105 lbs<br>(48 kg)   | 52.5 lbs<br>(24 kg) | 110 lbs<br>(50 kg) | 55 lbs<br>(25 kg) | 200 lbs<br>(90 kg) | 100 lbs<br>(45 kg) |

**Specifications:**

| Black foam seal  |   |
|--|---|
| Material   | SBR rubber foam sponge                            |
| Color  | Black   |
| L x W x H  | 16.2 x 4.5 x 1.24" (411 x 115 x 31.5 mm)          |
| Dimensions of seal   | 371 x 65 mm                                       |
| Density  | 10.6 lbs/cu ft (270 kg/m <sup>3</sup> )           |
| Hardness, Shore C  | ~30 x ±2  |
| Tearing Pressure   | 1800 Psi (124 kg/cm <sup>2</sup> )                |
| Compression to 25% size at 1000psi (Compressive 48% performance reduction) | 8.5 Psi (6000 kg/m <sup>2</sup> )                 |
| Water Absorption, %  | <±5   |
| Shrinkage at 160F (70C) for 24 hrs, %                                      | <±20  |
| Recommended Storage Temperature  | Room temperature                                  |
| Red seal   |   |
| Material   | Silicon Foam                                      |
| Color  | Red   |
| Density  | 43.1 lbs/cu ft (1050 kg/m <sup>3</sup> )          |
| Hardness, Shore C  | 50-41-5   |
| Water Absorption, %  | <±4   |
| Recommended Storage Temperature  | Room temperature                                  |
| Full seal  |   |
| Features   | Composed seal on plastic frame<br>Slender profile |